



500 OHMS / FT | Ni-Cr Alloy | Kevlar® Core | 100:1 Turn Ratio | 600-2000°F



150 OHMS / FT | Cu-Ni Alloy | Kevlar® Core | 100:1 Turn Ratio | 600-2000°F



40 OHMS / FT | Copper Alloy | Kevlar® Core | 200:1 Turn Ratio | 600-2000°F

**EMI / RFI SUPPRESSION | SPIRAL WOUND DESIGN
100% SILICONE SLEEVE | FIBERGLASS REINFORCED**



DRAGON FIRE Performance™
HIGH PERFORMANCE TECHNOLOGY

**ISO 9001:2015
IATF 16949:2016**

| STREET SERIES - 500 OHM/FT | | | BOOT CONSTRUCTION | | |
|----------------------------|-----------|------------|-------------------|-----------------------|-----------------------|
| SPARK PLUG BOOT ANGLE | CYLINDERS | WIRE COLOR | SILICONE 600° F | WHITE CERAMIC 2000° F | BLACK CERAMIC 2000° F |
| 90° DEGREE | 8 CYL. | RED * | SPW1001-RD | SPW1001WC-RD | SPW1001BC-RD |
| 180° DEGREE | 8 CYL. | RED * | SPW1002-RD | SPW1002WC-RD | SPW1002BC-RD |
| 135° DEGREE | 8 CYL. | RED * | SPW1003-RD | SPW1003WC-RD | SPW1003BC-RD |
| 90° DEGREE | 8 CYL. | BLACK * | SPW1001-BK | SPW1001WC-BK | SPW1001BC-BK |
| 180° DEGREE | 8 CYL. | BLACK * | SPW1002-BK | SPW1002WC-BK | SPW1002BC-BK |
| 135° DEGREE | 8 CYL. | BLACK * | SPW1003-BK | SPW1003WC-BK | SPW1003BC-BK |

*wire lengths: 2x53" 2x49.5" 2x38" 2x33.5" 1x36" (Coil Wire)

***FOR HEI & SOCKET CAP**

*wire diameter: 8.5mm

| SPORT SERIES - 150 OHM/FT | | | BOOT CONSTRUCTION | | |
|---------------------------|-----------|------------|-------------------|-----------------------|-----------------------|
| SPARK PLUG BOOT ANGLE | CYLINDERS | WIRE COLOR | SILICONE 600° F | WHITE CERAMIC 2000° F | BLACK CERAMIC 2000° F |
| 90° DEGREE | 8 CYL. | RED * | SPW2001-RD | SPW2001WC-RD | SPW2001BC-RD |
| 180° DEGREE | 8 CYL. | RED * | SPW2002-RD | SPW2002WC-RD | SPW2002BC-RD |
| 135° DEGREE | 8 CYL. | RED * | SPW2003-RD | SPW2003WC-RD | SPW2003BC-RD |
| 90° DEGREE | 8 CYL. | BLACK * | SPW2001-BK | SPW2001WC-BK | SPW2001BC-BK |
| 180° DEGREE | 8 CYL. | BLACK * | SPW2002-BK | SPW2002WC-BK | SPW2002BC-BK |
| 135° DEGREE | 8 CYL. | BLACK * | SPW2003-BK | SPW2003WC-BK | SPW2003BC-BK |

*wire lengths: 2x53" 2x49.5" 2x38" 2x33.5" 1x36" (Coil Wire)

***FOR HEI & SOCKET CAP**

*wire diameter: 8.5mm

| RACE SERIES - 40 OHM/FT | | | BOOT CONSTRUCTION | | |
|-------------------------|-----------|------------|-------------------|-----------------------|-----------------------|
| SPARK PLUG BOOT ANGLE | CYLINDERS | WIRE COLOR | SILICONE 600° F | WHITE CERAMIC 2000° F | BLACK CERAMIC 2000° F |
| 90° DEGREE | 8 CYL. | RED * | SPW3001-RD | SPW3001WC-RD | SPW3001BC-RD |
| 180° DEGREE | 8 CYL. | RED * | SPW3002-RD | SPW3002WC-RD | SPW3002BC-RD |
| 135° DEGREE | 8 CYL. | RED * | SPW3003-RD | SPW3003WC-RD | SPW3003BC-RD |
| 90° DEGREE | 8 CYL. | BLACK * | SPW3001-BK | SPW3001WC-BK | SPW3001BC-BK |
| 180° DEGREE | 8 CYL. | BLACK * | SPW3002-BK | SPW3002WC-BK | SPW3002BC-BK |
| 135° DEGREE | 8 CYL. | BLACK * | SPW3003-BK | SPW3003WC-BK | SPW3003BC-BK |

*wire lengths: 2x53" 2x49.5" 2x38" 2x33.5" 1x36" (Coil Wire)

***FOR HEI & SOCKET CAP**

*wire diameter: 8.5mm



| UNIVERSAL FIT - OE COIL LOCATION OR RELOCATED | | | BOOT CONSTRUCTION | | |
|---|-----------|------------|--------------------|--------------------------|--------------------------|
| SPARK PLUG BOOT ANGLE | CYLINDERS | WIRE COLOR | SILICONE 600° F | WHITE CERAMIC 2000° F | BLACK CERAMIC 2000° F |
| LS SERIES 135° - STREET SERIES | 8 CYL. | RED * | SPW 1004-RD | SPW 1004WC-RD | SPW1004BC-RD |
| LS SERIES 135° - STREET SERIES | 8 CYL. | BLACK * | SPW 1004-BK | SPW 1004WC-BK | SPW 1004BC-BK |
| LS SERIES 135° - SPORT SERIES | 8 CYL. | RED * | SPW 2004-RD | SPW 2004WC-RD | SPW2004BC-RD |
| LS SERIES 135° - SPORT SERIES | 8 CYL. | BLACK * | SPW 2004-BK | SPW 2004WC-BK | SPW 2004BC-BK |
| LS SERIES 135° - RACE SERIES | 8 CYL. | RED * | SPW 3004-RD | SPW 3004WC-RD | SPW3004BC-RD |
| LS SERIES 135° - RACE SERIES | 8 CYL. | BLACK * | SPW 3004-BK | SPW 3004WC-BK | SPW 3004BC-BK |

*wire lengths: 2x53" 2x49.5" 2x38" 2x33.5"

*wire diameter: 8.5mm

| DIRECT FIT LS SERIES | | | BOOT CONSTRUCTION | | |
|---|--------|-----------------|-------------------|-----------|---------------|
| FITMENT | LENGTH | WIRE COLOR | WIRE SIZE | CONDUCTOR | |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | RED * | 8.5mm | STREET | SPW1005HS-RD |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | YELLOW * | 8.5mm | STREET | SPW 1005 HS-Y |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | BLUE * | 8.5mm | STREET | SPW1005HS-BL |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | ORANGE * | 8.5mm | STREET | SPW 1005 HS-O |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | SILVER * | 8.5mm | STREET | SPW 1005 HS-S |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | HIGH TEMP RED * | 13mm | STREET | SPW1007 |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | RED * | 10mm | SPORT | SPW 2005-RD |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | HIGH TEMP RED * | 13mm | SPORT | SPW2007 |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | HIGH TEMP RED * | 13mm | RACE | SPW3007 |
| 135° BOOT 1997-2019 LS SERIES LS1 LS2 LS3 LS6 LS7 LSA | 9.5" | SILVER * | 10mm | RACE | SPW 3005-S |

*High-Temp wires rated to 1300°F

| ACCESSORIES | | | |
|---|-----------|---------------------------|----------|
| DESCRIPTION | CYLINDERS | FITMENT | |
| LS IGNITION COIL BOOT / TERMINAL KIT | 8 CYL. | 1997-2019 LS TRUCK/CAR | SPW 1006 |
| | | | |

*fits 7mm-8.5mm diameter wire

TECH HELP

For assistance with product information, installation, and general technical inquiries, contact us:

Write Us: help@dragonfireperformance.com

Call Us: 888-732-7718 ext. 700 (M-F 9am-4pm PST)

