

NEW FROM ISKY....PART NO. 1410ML

SMALL DIAMETER "MAX-LIFE" DUAL W/DAMPER VALVE SPRING

**Better HFD™ (High Frequency Dynamics)
Than Any Other Low-Mass Design**



Designed for maximum endurance in sustained high RPM dirt late model applications employing super lightweight valve components: (7mm diameter intake and 5/16" diameter exhaust valves) along with titanium valve locks, lightweight "tool steel" retainers and large dia/heavy wall pushrods. Coupled with the above components, the natural frequency separation of the Centrifugally Dampened™ #1410ML yields superior valve control over any current valve spring designs.

MAX-LIFE SERIES VALVE SPRING SPECIFICATIONS

Part Number	Description	Outer OD	Outer ID	Inner OD	Inner ID	Seat Pressure	Open Pressure	Rate Per Inch	Max Net Lift	Coil Bind	Spring Mass	Jobber Price
1410ML	Dual w/Damper	1.410"	.986"	.899"	.615"	180 lbs @ 2.050"	760 lbs @ 1.220"	700	.830"	1.160"	141 Gr.	\$675.00

Part Number	Description	Jobber Price
100VSL	Chrome Moly Valve Spring Locaters for .565" Dia. Valve Guides, .050" Thick (Set/16)	\$150.00
41ST	Lightweight "Tool Steel" Retainers. 16 Grams each (Set 16) w/.050" Step for Inner Spring: Use with Min-8/500 Gauge Titanium Valve Locks.	\$460.00

DO IT RIGHT...



...RACE WITH
THE LEGEND

ED ISKENDERIAN RACING CAMS

16020 S. BROADWAY • GARDENA, CALIFORNIA 90247-9990 • (310) 217-9232 • FAX (310) 515-5730

For the most up to date information on new products, visit us at our website: www.iskycams.com