

DO IT RIGHT...



...RACE WITH THE LEGEND

Introducing the NEW ML “MAX-LIFE” Super Endurance Roller Valve Spring Series

Designed for use in the most grueling, sustained Hi-RPM oval track environments, the “MAX-LIFE” super endurance series are manufactured from a revolutionary new alloy steel. They employ precision nitride heat treating and a multi-stage, micro-polished “MAX-LIFE” surface finish to enhance their longevity in the most aggressive endurance racing applications.



MAX-LIFE SERIES VALVE SPRING SPECIFICATIONS

| Part Number | Description | Outer OD | Outer ID | Inner OD | Inner ID | Seat Pressure | Open Pressure | Rate Per Inch | Max Net Lift | Coil Bind |
|---------------|---------------|----------|----------|----------|----------|------------------|------------------|---------------|--------------|-----------|
| 1410ML | Dual w/Damper | 1.410" | .986" | .899" | .615" | 180 lbs @ 2.050" | 760 lbs @ 1.220" | 700 | .830" | 1.160" |
| 9987RADML | Dual w/Damper | 1.570" | 1.146" | 1.044" | .748" | 275 lbs @ 2.000" | 790 lbs @ 1.200" | 644 | .800" | 1.150" |
| 9996RADML | Dual w/Damper | 1.600" | 1.150" | 1.040" | .745" | 275 lbs @ 2.050" | 810 lbs @ 1.200" | 625 | .850" | 1.150" |
| 1511 (PSI) | Beehive LS | 1.290" | .630" | N/A | N/A | 130 lbs @ 1.800" | 370 lbs @ 1.175" | 384 | .625" | 1.100" |
| 1516 (PSI) | Beehive LS | 1.290" | .640" | N/A | N/A | 150 lbs @ 1.800" | 420 lbs @ 1.140" | 409 | .660" | 1.080" |
| 1540ML (PSI) | Dual | 1.500" | 1.085" | N/A | .790" | 250 lbs @ 2.030" | 610 lbs @ 1.250" | 462 | .780" | 1.180" |
| 1542ML (PSI) | Dual | 1.580" | 1.160" | N/A | .835" | 248 lbs @ 2.050" | 640 lbs @ 1.270" | 503 | .780" | 1.200" |
| 1574ML (PSI) | Dual | 1.510" | 1.085" | N/A | .760" | 180 lbs @ 1.980" | 680 lbs @ 1.180" | 625 | .800" | 1.110" |
| 1575ML (PSI) | Dual | 1.400" | .995" | N/A | .700" | 150 lbs @ 2.000" | 625 lbs @ 1.150" | 559 | .850" | 1.100" |
| 1577DML (PSI) | Dual w/Damper | 1.550" | 1.100" | .985" | .706" | 295 lbs @ 2.000" | 860 lbs @ 1.200" | 706 | .800" | 1.150" |
| 1578ML (PSI) | Dual | 1.378" | .976" | N/A | .680" | 150 lbs @ 2.000" | 640 lbs @ 1.150" | 576 | .850" | 1.110" |
| 1579ML (PSI) | Dual | 1.420" | .996" | N/A | .700" | 240 lbs @ 2.100" | 834 lbs @ 1.200" | 660 | .900" | 1.160" |

We are proud to announce that Isky has recently been appointed a Distributor for **PSI Sportsman Drag Race Valve Springs**.

You can trust **PSI** (Performance Springs Inc.) Valve Springs to out-perform all others because they are exclusively 100% American Made using the finest materials, the best CNC Equipment and state of the art trade secret processing.

Don't settle for those foreign made springs of lesser quality. Insist on Genuine **PSI** Drag Race Valve Springs and get into the winners circle!

Isky Stocks the following **PSI** Part numbers.



DRAG SERIES VALVE SPRING SPECIFICATIONS

| Part Number | Description | Outer OD | Outer ID | Middle ID | Inner ID | Seat Pressure | Open Pressure | Rate Per Inch | Max Net Lift | Coil Bind |
|-------------|---------------|----------|----------|-----------|----------|------------------|-------------------|---------------|--------------|-----------|
| 424R | Dual | 1.525" | 1.100" | N/A | .780" | 250 lbs @ 2.000" | 775 lbs @ 1.200" | 656 | .800" | 1.140" |
| 425R | Dual | 1.625" | 1.175" | N/A | .855" | 305 lbs @ 2.050" | 865 lbs @ 1.150" | 622 | .900" | 1.100" |
| 426R | Dual | 1.500" | 1.075" | N/A | .765" | 300 lbs @ 2.050" | 840 lbs @ 1.150" | 600 | .900" | 1.100" |
| 1201D | Single w/damp | 1.260" | .857" | N/A | N/A | 150 lbs @ 1.750" | 488 lbs @ 1.200" | 564 | .600" | 1.100" |
| 1224 | Dual | 1.625" | 1.175" | N/A | .855" | 275 lbs @ 2.000" | 750 lbs @ 1.200" | 594 | .800" | 1.130" |
| 1246 | Triple | 1.645" | 1.195" | .870" | .630" | 300 lbs @ 2.000" | 890 lbs @ 1.200" | 738 | .800" | 1.100" |
| 1247 | Triple | 1.660" | 1.195" | .870" | .630" | 340 lbs @ 2.070" | 940 lbs @ 1.270" | 750 | .800" | 1.130" |
| 1248 | Triple | 1.660" | 1.195" | .870" | .630" | 375 lbs @ 2.100" | 1045 lbs @ 1.200" | 744 | .900" | 1.130" |
| 1249 | Triple | 1.660" | 1.195" | .870" | .630" | 385 lbs @ 2.200" | 1110 lbs @ 1.200" | 725 | 1.000" | 1.130" |
| 1250 | Triple | 1.660" | 1.195" | .870" | .630" | 395 lbs @ 2.250" | 1178 lbs @ 1.200" | 746 | 1.050" | 1.130" |
| 1251 | Triple | 1.660" | 1.195" | .870" | .630" | 395 lbs @ 2.300" | 1176 lbs @ 1.250" | 744 | 1.050" | 1.130" |

New Max-Life Super Endurance Drag Roller Valve Spring Series

PSI's engineers used the latest advancements in valve spring material technology to create the ultimate high strength material used in drag racing called the ML series. The ML series includes a few of their original valve spring designs along with many new designs that utilize this high strength material. The ML series valve springs have been tested by many of the top teams and have proven to provide the ultimate in load retention capability. They employ the traditional Max-Life Polished Surface Enhanced Finish.



MAX-LIFE SERIES VALVE SPRING SPECIFICATIONS

| Part Number | Description | Outer OD | Outer ID | Middle ID | Inner ID | Seat Pressure | Open Pressure | Rate Per Inch | Max Net Lift | Coil Bind |
|-------------|-------------|----------|----------|-----------|----------|------------------|-------------------|---------------|--------------|-----------|
| 424 RML | Dual | 1.525" | 1.100" | N/A | .780" | 250 lbs @ 2.000" | 775 lbs @ 1.200" | 656 | .800" | 1.140" |
| 425 RML | Dual | 1.625" | 1.175" | N/A | .855" | 305 lbs @ 2.050" | 865 lbs @ 1.150" | 622 | .900" | 1.100" |
| 426 RML | Dual | 1.500" | 1.075" | N/A | .765" | 300 lbs @ 2.050" | 840 lbs @ 1.150" | 600 | .900" | 1.100" |
| 427 RML | Dual | 1.300" | .898" | N/A | .628" | 230 lbs @ 1.850" | 715 lbs @ 1.100" | 647 | .750" | 1.050" |
| 1224ML | Dual | 1.625" | 1.175" | .855" | | 275 lbs @ 2.000" | 750 lbs @ 1.200" | 594 | .800" | 1.130" |
| 1247ML | Triple | 1.660" | 1.195" | .870" | .630" | 340 lbs @ 2.070" | 940 lbs @ 1.270" | 750 | .800" | 1.130" |
| 1248ML | Triple | 1.660" | 1.195" | .870" | .630" | 375 lbs @ 2.100" | 1045 lbs @ 1.200" | 744 | .900" | 1.130" |
| 1249ML | Triple | 1.660" | 1.195" | .870" | .630" | 385 lbs @ 2.200" | 1110 lbs @ 1.200" | 725 | 1.000" | 1.130" |
| 1250ML | Triple | 1.660" | 1.195" | .870" | .630" | 395 lbs @ 2.250" | 1178 lbs @ 1.200" | 746 | 1.050" | 1.130" |
| 1251ML | Triple | 1.660" | 1.195" | .870" | .630" | 395 lbs @ 2.300" | 1176 lbs @ 1.250" | 744 | 1.050" | 1.130" |
| 1253 RML | Triple | 1.630" | 1.180" | .870" | .630" | 440 lbs @ 2.200" | 1200 lbs @ 1.150" | 724 | 1.050" | 1.080" |
| 1254 RML | Dual | 1.520" | 1.070" | N/A | .745" | 350 lbs @ 2.100" | 1040 lbs @ 1.200" | 767 | .900" | 1.140" |
| 1255 RML | Dual | 1.520" | 1.070" | N/A | .745" | 445 lbs @ 2.200" | 1170 lbs @ 1.200" | 725 | 1.000" | 1.140" |
| 1256 RML | Dual | 1.540" | 1.070" | N/A | .745" | 390 lbs @ 2.200" | 1250 lbs @ 1.200" | 860 | 1.000" | 1.140" |
| 1258 RML | Dual | 1.530" | 1.065" | N/A | .726" | 430 lbs @ 2.200" | 1375 lbs @ 1.200" | 945 | 1.000" | 1.140" |
| 1259 RML | Dual | 1.520" | 1.070" | N/A | .730" | 375 lbs @ 2.150" | 1154 lbs @ 1.200" | 820 | .950" | 1.140" |
| 1260 RML | Triple | 1.675" | 1.195" | .870" | .630" | 465 lbs @ 2.300" | 1295 lbs @ 1.250" | 790 | 1.050" | 1.140" |
| 1261 RML | Triple | 1.675" | 1.195" | .870" | .630" | 510 lbs @ 2.300" | 1315 lbs @ 1.250" | 767 | 1.050" | 1.140" |
| 1263 RML | Triple | 1.675" | 1.195" | .870" | .630" | 425 lbs @ 2.400" | 1355 lbs @ 1.250" | 809 | 1.150" | 1.100" |
| 1264 RML | Triple | 1.710" | 1.210" | .870" | .630" | 380 lbs @ 2.550" | 1530 lbs @ 1.250" | 885 | 1.300" | 1.140" |
| 1267 RML | Triple | 1.740" | 1.240" | .880" | .630" | 400 lbs @ 2.550" | 1600 lbs @ 1.250" | 923 | 1.300" | 1.180" |
| 1268 RML | Triple | 1.710" | 1.210" | .870" | .630" | 500 lbs @ 2.400" | 1612 lbs @ 1.250" | 967 | 1.150" | 1.140" |
| 1280 RML | Dual | 1.520" | 1.070" | N/A | .730" | 445 lbs @ 2.200" | 1230 lbs @ 1.200" | 785 | 1.000" | 1.140" |
| 1281 RML | Dual | 1.540" | 1.070" | N/A | .730" | 390 lbs @ 2.200" | 1310 lbs @ 1.200" | 920 | 1.000" | 1.140" |



ED ISKENDERIAN RACING CAMS
16020 S. BROADWAY GARDENA, CALIFORNIA 90247-9990
(310) 217-9232 FAX (310) 515-5730

For the most up to date information on new products, visit us at our website: www.iskycams.com